

1" Turbojet Nozzles

- Flow setting at 100 psi (7 bar) operating pressure can be used for high pressure applications up to 580 psi (40 bar) hydrostatic pressure
- Raised bumper lug for straight stream pattern identification
- Compatible with Quick-Attack Foam Tube Style 755, See page 21

- 1701** 1" Turbojet Nozzle
- 1702** 1" Turbojet Nozzle with Pistol Grip
- 1703** 1" Turbojet Tip
 - For use on Style 753 shutoff
- 1704** 1" Turbojet Nozzle with Pistol Grip
- 1711** 1" Turbojet Tip
 - For use on Style 753 shutoff
 - Specify either 18-30 GPM or 13-23-30 GPM settings



Style 1702

Style	Swivel Inlet	Length	Weight lbs. (kg)	Flow Settings	
				GPM	LPM
1701	1 (25 mm)	9 1/4" (206 mm)	2 1/2 (1.1 kg)	13-25-40-60	50-100-150-230
1702	1" (25 mm)	9 1/4" (206 mm)	3 (1.4kg)	13-25-40-60	50-100-150-230
1703	1 1/2" (38 mm)	6 5/8" (14 mm)	1 3/4 (.8 kg)	13-25-40-60	50-100-150-230
1704	1" (25 mm)	9 1/4" (206 mm)	3 (1.4 kg)	18-30* 13-23-30*	70-115* 50-90-115*
1711	1 1/2" (38 mm)	6 5/8" (14 mm)	3 3/4 (1.7 kg)	18-30* 13-23-30*	70-115* 50-90-115*

*Must specify



1 1/2" Turbojet Nozzles

- 100 psi (7 bar) standard, 75 psi (5 & 6 bar) optional
- Compatible with Quick Attack Foam Tube Style 766, See page 21

- 1714** 1 1/2" Turbojet Tip
- 1715** 1 1/2" Turbojet Nozzle
- 1716** 1 1/2" Turbojet Breakapart Nozzle
 - Combination of Style 1717 tip + Style 2115 shutoff
- 1717** 1 1/2" Turbojet Tip with Twist Shutoff
- 1718** 1 1/2" Turbojet Breakapart Nozzle with Pistol Grip
 - Combination of Style 1717 tip + Style 2116 shutoff
- 1720** 1 1/2" Turbojet Nozzle with Pistol Grip



Style 1717



Style 1720

Style	Swivel Inlet	Length	Weight lbs. (kg)	Flow Settings	
				GPM	LPM
1714	1 1/2" (38 mm)	6 7/8" (165 mm)	2 1/4 (1 kg)	30-60-95-125	115-230-360-475
1715	1 1/2" (38 mm)	9 1/2" (232 mm)	3 1/2 (1.6 kg)	30-60-95-125	115-230-360-475
1716	1 1/2" (38 mm)	12" (295 mm)	3 3/4 (1.7 kg)	30-60-95-125	115-230-360-475
1717	1 1/2" (38 mm)	7 1/4" (175 mm)	2 1/4 (1 kg)	30-60-95-125	115-230-360-475
1718	1 1/2" (38 mm)	12" (295 mm)	4 1/8 (1.9 kg)	30-60-95-125	115-230-360-475
1720	1 1/2" (38 mm)	9 1/2" (232 mm)	4 (1.8 kg)	30-60-95-125	115-230-360-475



1 1/2" Electrical Turbojet Nozzles

- Designed to be used on class "C" hazards
- No straight stream capabilities (min. 30° fog)

- 1715E** 1 1/2" Electrical Turbojet Nozzle
- 1720E** 1 1/2" Electrical Turbojet Nozzle with Pistol Grip



Style 1720E

Style	Swivel Inlet	Length	Weight lbs. (kg)	Flow Settings	
				GPM	LPM
1715E	1 1/2" (38 mm)	9 1/2" (232 mm)	3 1/2 (1.6 kg)	30-60-95-125	115-230-360-475
1720E	1 1/2" (38 mm)	9 1/2" (232 mm)	4 (1.8 kg)	30-60-95-125	115-230-360-475

